


# External PSU output connector options

## Connector Selector



FiDUS Power externals are available with a wide range of standard output connector options, allowing customers the flexibility to use the connector that best fits their industry and product type.

- + Rapid prototypes 2-3days (Check availability)
- + Available for high & low volume applications

Select your external product series and see available connectors on the final page of the datasheet.

### XXX SERIES - [CONNECTOR SELECTOR]

	<b>Universal Simple</b>	5.5mm/2.1mm Straight Barrel Jack (11mm length)			<b>-P01K</b>
	<b>Universal Simple</b>	5.5mm/2.5mm Straight Barrel Jack (11mm length)			<b>-P01N</b>
	<b>Universal Simple</b>	5.5mm/2.1mm Straight Barrel Jack (9.5mm length)			<b>-P01J</b>
	<b>Universal Simple</b>	5.5mm/2.5mm Straight Barrel Jack (9.5mm length)			<b>-P01M</b>
	<b>Compact Tidy</b>	5.5mm/2.1mm Right Angle Jack (11mm length)			<b>-P02K</b>
	<b>Compact Tidy</b>	5.5mm/2.5mm Right Angle Jack (9mm length)			<b>-P02M</b>
	<b>Friction locking</b>	DIN-5 plug Friction locking Male			<b>-P05B</b>
	<b>Friction locking</b>	DIN-4 plug friction locking Male			<b>-P09B</b>
	<b>Modern Recognisable</b>	Micro USB Male			<b>-P88D</b>
	<b>Locking Unique</b>	Molex 43025-0600 or CVILUX CP35006S0010			<b>-P35C</b>

Still can't find your ideal connector? Contact sales for assistance

+44 (0)1183 420 730

sales@fiduspower.com