



QQHM2.E482078
Power Supplies, Medical and Dental - Component

Page Bottom

Power Supplies, Medical and Dental - Component

See General Information for Power Supplies, Medical and Dental - Component

FIDUS POWER LTD

E482078

Mars House Units 3-4

Calleva Park

Aldermaston, RG7 8LA UNITED KINGDOM

Model No.	Rated Input			Max Output				SP	EP	FC	GC
	Volts	Hz	SC	V	A	VA	OC				
AMM1505, QAMM1505, AMM1509, QAMM1509, AMM1512, QAMM1512, AMM1515, QAMM1515, AMM1524, QAMM1524											
	100-240ac	47-63	-	-	-	-	-	ANSI/AAMI ES 60601-1: 2005	20B	1	-
AMM2012, QAMM2012, AMM2024, QAMM2024											
	100-240ac	47-63	-	-	-	-	-	ANSI/AAMI ES 60601-1: 2005	20B	1	-
AMM3005, QAMM3005, AMM3012, QAMM3012, AMM3015, QAMM3015, AMM3024, QAMM3024											
	100-240ac	47-63	-	-	-	-	-	ANSI/AAMI ES 60601-1: 2005	20B	1	-
AMM4003, QAMM4003[*r]	100-240ac	47-63	0	3.3	8	-	9	ANSI/AAMI ES 60601-1: 2005	20B	0	2
AMM4005, QAMM4005	100-240ac	47-63	0	5.9	15	69.75	9	ANSI/AAMI ES 60601-1: 2005	20B	0	2
AMM4009, QAMM4009[*r]	100-240ac	47-63	0	9	4.444	-	9	ANSI/AAMI ES 60601-1: 2005	20B	0	2
AMM4012, QAMM4012[*r]	100-240ac	47-63	0	12	3.333	-	9	ANSI/AAMI ES 60601-1: 2005	20B	0	2
AMM4015, QAMM4015[*r]	100-240ac	47-63	0	15	2.666	-	9	ANSI/AAMI ES 60601-1: 2005	20B	0	2
AMM4024, QAMM4024	100-240ac	47-63	0	24.3	2.5	59.75	9	ANSI/AAMI ES 60601-1: 2005	20B	0	2
AMM40D01, QAMM40D01	100-240ac	47-63	0	5.1	11	38.5	9	ANSI/AAMI ES 60601-1: 2005	20B	0	2
				-5	11	37.4	9				
AMM40D02, QAMM40D02[*r]	100-240ac	47-63	0	12	1.666	-	9	ANSI/AAMI ES 60601-1: 2005	20B	0	2
				-12	1.666	-	9				
AMM40D03, QAMM40D03	100-240ac	47-63	0	15	3.9	44.46	9	ANSI/AAMI ES 60601-1: 2005	20B	0	2
				-15	3.9	44.46	9				
AMM40D04, QAMM40D04[*r]	100-240ac	47-63	0	5	5	-	9	ANSI/AAMI ES 60601-1: 2005	20B	0	2
				12	1.25	-	9				
AMM40D05, QAMM40D05	100-240ac	47-63	0	5.5	10.9	50.4	9	ANSI/AAMI ES 60601-1: 2005	20B	0	2
				31.1	1.2	27.7	9				
AMM40T01	100-240ac	47-63	0	5.83	10.41	49.66	9	ANSI/AAMI ES 60601-1: 2005	20B	0	2
				14.77	3.98	33.4	9				
				-14.83	3.68	33.5	9				

AMM40T02	100-240ac	47-63	0	5.6	4.8	50.9	9	ANSI/AAMI ES 60601-1: 2005	20B	0	2
				18.5	2.65	29.4	9				
				-18.8	2.3	30.15	9				
AMM6005, QAMM6005, AMM6009, QAMM6009, AMM6012, QAMM6012, AMM6015, QAMM6015, AMM6024, QAMM6024											
	100-240ac	47-63	-	-	-	-	-	ANSI/AAMI ES 60601-1: 2005	20B	1	-
MDT18012 (A2) [*r]	100-240Vac	47-63	0	12	14	168	9	ES60601-1 A1	20B	0	1
MDT18012-C2 (A2) [*r]	100-240 Vac	47-63	0	12dc	14	Max. 168 W	16	ES60601-1 A1	20B	0	2
MDT18019 (A2) [*r]	100-240Vac	47-63	0	19	9.47	180	9	ES60601-1 A1	20B	0	1
MDT18019-C2 (A2) [*r]	100-240 Vac	47-63	0	19dc	9.47	Max. 180 W	16	ES60601-1 A1	20B	0	2
MDT18024 (A2) [*r]	100-240Vac	47-63	0	24	7.5	180	9	ES60601-1 A1	20B	0	1
MDT18024-C2 (A2) [*r]	100-240 Vac	47-63	0	24dc	7.5	Max. 180 W	16	ES60601-1 A1	20B	0	2
MDT18030 (A2) [*r]	100-240Vac	47-63	0	30	6	180	9	ES60601-1 A1	20B	0	1
MDT18030-C2 (A2) [*r]	100-240 Vac	47-63	0	30dc	6	Max. 180 W	16	ES60601-1 A1	20B	0	2
MDT18033 (A2) [*r]	100-240Vac	47-63	0	33	5.45	180	9	ES60601-1 A1	20B	0	1
MDT18033-C2 (A2) [*r]	100-240 Vac	47-63	0	33dc	5.45	Max. 180 W	16	ES60601-1 A1	20B	0	2
MDT18048 (A2) [*r]	100-240Vac	47-63	0	48	3.75	180	9	ES60601-1 A1	20B	0	1
MDT18048-C2 (A2) [*r]	100-240 Vac	47-63	0	48dc	3.75	Max. 180 W	16	ES60601-1 A1	20B	0	2
MDT3005-C18, MDT3005-C2 (A3)											
	100-240ac	47-63	0	5.3	5.5	25.8	9	ANSI/AAMI ES 60601-1: 2005	20B	0	2
MDT3007-C18, MDT3007-C2 (A3) [*r]											
	100-240ac	47-63	0	7.0	3.3	23	9	ANSI/AAMI ES 60601-1: 2005	20B	0	2
MDT3009-C18, MDT3009-C2 (A3) [*r]											
	100-240ac	47-63	0	9.0	2.0	27	9	ANSI/AAMI ES 60601-1: 2005	20B	0	2
MDT3012-C18, MDT3012-C2 (A3)											
	100-240ac	47-63	0	11.1	3.8	40.9	9	ANSI/AAMI ES 60601-1: 2005	20B	0	2
MDT3015-C18, MDT3015-C2 (A3) [*r]											
	100-240ac	47-63	0	15.0	2.0	30.0	9	ANSI/AAMI ES 60601-1: 2005	20B	0	2
MDT3018-C18, MDT3018-C2 (A3) [*r]											
	100-240ac	47-63	0	18.0	1.67	30.0	9	ANSI/AAMI ES 60601-1: 2005	20B	0	2
MDT3024-C18, MDT3024-C2 (A3) [*r]											
	100-240ac	47-63	0	24	1.25	30	9	ANSI/AAMI ES 60601-1: 2005	20B	0	2
MDT3030-C18, MDT3030-C2 (A3) [*r]											
	100-240ac	47-63	0	30	1.0	30	9	ANSI/AAMI ES 60601-1: 2005	20B	0	2
MDT3036-C18, MDT3036-C2 (A3) [*r]											
	100-240ac	47-63	0	36.9	0.83	30	9	ANSI/AAMI ES 60601-1: 2005	20B	0	2

MDT3048-C18, MDT3048-C2 (A3)											
	100-240ac	47-63	0	48.2	0.8	39.2	9	ANSI/AAMI ES 60601-1: 2005	20B	0	2
MDT6012-C14, MDT6012-C6 (A2)[*r]											
	100-240ac	47-63	0	12dc	5.25	63	16	ANSI/AAMI ES 60601-1: 2005; ES60601-1 A1	20B	0	1
MDT6012-C2 (A2) [*r]	100-240ac	47-63	0	12dc	5.25	63	16	ANSI/AAMI ES 60601-1: 2005; ES60601-1 A1	20B	0	1
MDT6015-C14, MDT6015-C6 (A2)[*r]											
	100-240ac	47-63	0	15dc	4.20	63	16	ANSI/AAMI ES 60601-1: 2005; ES60601-1 A1	20B	0	1
MDT6015-C2 (A2) [*r]	100-240ac	47-63	0	15dc	4.20	63	16	ANSI/AAMI ES 60601-1: 2005; ES60601-1 A1	20B	0	1
MDT6018-C14, MDT6018-C6 (A2)[*r]											
	100-240ac	47-63	0	18dc	3.50	63	16	ANSI/AAMI ES 60601-1: 2005; ES60601-1 A1	20B	0	1
MDT6018-C2 (A2) [*r]	100-240ac	47-63	0	18dc	3.50	63	16	ANSI/AAMI ES 60601-1: 2005; ES60601-1 A1	20B	0	1
MDT6024-C14, MDT6024-C6 (A2)[*r]											
	100-240ac	47-63	0	24dc	2.62	63	16	ANSI/AAMI ES 60601-1: 2005; ES60601-1 A1	20B	0	1
MDT6024-C2 (A2) [*r]	100-240ac	47-63	0	24dc	2.62	63	16	ANSI/AAMI ES 60601-1: 2005; ES60601-1 A1	20B	0	1
MDT6030-C14, MDT6030-C6 (A2)[*r]											
	100-240ac	47-63	0	30dc	2.10	63	16	ANSI/AAMI ES 60601-1: 2005; ES60601-1 A1	20B	0	1
MDT6030-C2 (A2) [*r]	100-240ac	47-63	0	30dc	2.10	63	16	ANSI/AAMI ES 60601-1: 2005; ES60601-1 A1	20B	0	1
MDT6036-C14, MDT6036-C6 (A2)[*r]											
	100-240ac	47-63	0	36dc	1.75	63	16	ANSI/AAMI ES 60601-1: 2005; ES60601-1 A1	20B	0	1
MDT6036-C2 (A2) [*r]	100-240ac	47-63	0	36dc	1.75	63	16	ANSI/AAMI ES 60601-1: 2005; ES60601-1 A1	20B	0	1
MDT6048-C14, MDT6048-C6 (A2)[*r]											
	100-240ac	47-63	0	48dc	1.31	63	16	ANSI/AAMI ES 60601-1: 2005; ES60601-1 A1	20B	0	1
MPT1503 (A2) [*r]	100~240ac	47-63	0	3~4.99dc	2.4~1.44	7.2	16	ES60601-1	20B	0	2
MPT1505 (A2) [*r]	100~240ac	47-63	0	5~5.99dc	2.4~2	12	16	ES60601-1	20B	0	2
MPT1507 (A2) [*r]	100~240ac	47-63	0	6.5~8dc	1.84~1.5	12	16	ES60601-1	20B	0	2
MPT1509 (A2) [*r]	100~240ac	47-63	0	8~11dc	1.68~1.22	13.5	16	ES60601-1	20B	0	2
MPT1512 (A2) [*r]	100~240ac	47-63	0	11~13dc	1.36~1.15	15	16	ES60601-1	20B	0	2
MPT1515 (A2) [*r]	100~240ac	47-63	0	13~16dc	1.15~0.94	15	16	ES60601-1	20B	0	2
MPT1518 (A2) [*r]	100~240ac	47-63	0	16~21dc	0.94~0.72	15	16	ES60601-1	20B	0	2
	100~240ac		0	21~27dc	0.72~0.55	15	16	ES60601-1	20B	0	2

MPT1524 (A2) [*r]		47-63										
MPT1528 (A2) [*r]	100~240ac	47-63	0	27~33dc	0.55~0.45	15	16	ES60601-1	20B	0	2	
MPT1536 (A2) [*r]	100~240ac	47-63	0	33~40dc	0.45~0.37	15	16	ES60601-1	20B	0	2	
MPT1548 (A2) [*r]	100~240ac	47-63	0	40~48dc	0.37~0.32	15	16	ES60601-1	20B	0	2	
MPT1554 (A2) [*r]	100~240ac	47-63	0	48~55dc	0.32~0.28	15	16	ES60601-1	20B	0	2	
MPT2503[*r]	100-240 Vac	47-63	0	3-5Vdc	3.5-2.1	10.5W	16	ANSI/AAMI ES 60601-1: 2005	20B	0	2	
MPT2505[*r]	100-240 Vac	47-63	0	5-6Vdc	3.3-2.75	16.5W	16	ANSI/AAMI ES 60601-1: 2005	20B	0	2	
MPT2507[*r]	100-240 Vac	47-63	0	6-8Vdc	3.3-2.5	20W	16	ANSI/AAMI ES 60601-1: 2005	20B	0	2	
MPT2509[*r]	100-240 Vac	47-63	0	8-11Vdc	2.75-2.0	22W	16	ANSI/AAMI ES 60601-1: 2005	20B	0	2	
MPT2512[*r]	100-240 Vac	47-63	0	11-13Vdc	2.27-1.92	25W	16	ANSI/AAMI ES 60601-1: 2005	20B	0	2	
MPT2515[*r]	100-240 Vac	47-63	0	13-16Vdc	1.92-1.56	25W	16	ANSI/AAMI ES 60601-1: 2005	20B	0	2	
MPT2518[*r]	100-240 Vac	47-63	0	16-21Vdc	1.56-1.19	25W	16	ANSI/AAMI ES 60601-1: 2005	20B	0	2	
MPT2524[*r]	100-240 Vac	47-63	0	21-27Vdc	1.19-0.92	25W	16	ANSI/AAMI ES 60601-1: 2005	20B	0	2	
MPT2528[*r]	100-240 Vac	47-63	0	27-33Vdc	0.92-0.75	25W	16	ANSI/AAMI ES 60601-1: 2005	20B	0	2	
MPT2536[*r]	100-240 Vac	47-63	0	33-40Vdc	0.75-0.62	25W	16	ANSI/AAMI ES 60601-1: 2005	20B	0	2	
MPT2548[*r]	100-240 Vac	47-63	0	40-48Vdc	0.62-0.53	25W	16	ANSI/AAMI ES 60601-1: 2005	20B	0	2	
MPT2554[*r]	100-240 Vac	47-63	0	48-55Vdc	0.52-0.45	25W	16	ANSI/AAMI ES 60601-1: 2005	20B	0	2	
TCF6505ZZZ (#)	100-240ac	50-60	0	5	8	65 W	16	ANSI/AAMI ES 60601-1: 2005	20B	0	0	
TCF6512ZZZ (#)	100-240ac	50-60	0	12.0	5.416	65 W	16	ANSI/AAMI ES 60601-1: 2005	20B	0	0	
TCF6515ZZZ (#)	100-240ac	50-60	0	15.0	4.333	65 W	16	ANSI/AAMI ES 60601-1: 2005	20B	0	0	
TCF6519ZZZ (#)	100-240ac	50-60	0	19.0	3.421	65 W	16	ANSI/AAMI ES 60601-1: 2005	20B	0	0	
TCF6524ZZZ (#)	100-240ac	50-60	0	24.0	2.708	65 W	16	ANSI/AAMI ES 60601-1: 2005	20B	0	0	
TCF6528ZZZ (#)	100-240ac	50-60	0	28.0	2.321	65 W	16	ANSI/AAMI ES 60601-1: 2005	20B	0	0	
TCF6530ZZZ (#)	100-240ac	50-60	0	30.0	2.167	65 W	16	ANSI/AAMI ES 60601-1: 2005	20B	0	0	
TCF6532ZZZ (#)	100-240ac	50-60	0	32.0	2.031	65 W	16	ANSI/AAMI ES 60601-1: 2005	20B	0	0	
TCF6536ZZZ (#)	100-240ac	50-60	0	36.0	1.806	65 W	16	ANSI/AAMI ES 60601-1: 2005	20B	0	0	
TCF6542ZZZ (#)	100-240ac	50-60	0	42.0	1.548	65 W	16	ANSI/AAMI ES 60601-1: 2005	20B	0	0	
TCF6548ZZZ (#)	100-240ac	50-60	0	48.0	1.354	65 W	16	ANSI/AAMI ES 60601-1: 2005	20B	0	0	
TCF6556ZZZ (#)	100-240ac	50-60	0	56.0	1.161	65 W	16	ANSI/AAMI ES 60601-1: 2005	20B	0	0	
VKL28012TZZ (#)	100 - 240ac	50-60	0	12dc	23.33	280	9,16	ES60601-1 A1	20B	0	1	
VKL28024ZZZ (#)	100 - 240ac	50-60	0	24dc	11.66	280	9,16	ES60601-1 A1	20B	0	1	

VKL28028ZZZ (#)	100 - 240ac	50- 60	0	28dc	10	280	9,16	ES60601-1 A1	20B	0	1
VKL28048ZZZ (#)	100 - 240ac	50- 60	0	48dc	5.83	280	9,16	ES60601-1 A1	20B	0	1
VKL28054ZZZ (#)	100 - 240ac	50- 60	0	54dc	5.18	280	9,16	ES60601-1 A1	20B	0	1

[*r] - Output values are rated.

(#) - Z = Any alphanumeric character, ?-?, or blank

(A2) - product certified to ANSI/AAMI ES60601-1: A1:2012 and CAN/CSA-C22.2 No. 60601-1 (2014)

(A3) - Product also certified to ANSI/AAMI ES60601-1 (2005/(R)2012 + A1:2012, C1:2009/(R)2012 + A2:2010/(R)2012) and CAN/CSA-C22.2 No. 60601-1:14.

Marking: Company name and model designation.

Last Updated on 2017-05-17

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".